

1  
2  
3  
4  
5  
6  
7  
8

1. An apparatus used with an electronic camera of the type associated with an electronic shutter which controls an image sensor, the apparatus comprising image size detection circuitry, which is responsive to electrical signals received from the electronic camera, for determining an actual image area within a total image area of the image sensor, and generating a control signal, based on the actual image area, for controlling the electronic shutter.

1  
2  
3  
4  
5  
6  
7

2. The apparatus of claim 1 wherein the electronic camera has a plurality of predefined shutter response areas, each shutter response area defining different portions of the total image area of the image sensor, said control signal selecting one of the shutter response areas, and said electronic shutter controlling said image sensor in response to the selected one of the shutter response areas.

1  
2  
3  
4

3. The apparatus of claim 2 further comprising a processor and a memory for storing data associated with the plurality of predefined shutter response areas of the electronic camera.

1  
2  
3  
4  
5

4. The apparatus of claim 3 wherein the electrical signals includes a luminance component used by the image size detection circuitry to determine the portion of the total image area of the image sensor containing the actual image.

1        5. The apparatus of claim 4 wherein the image  
 2 detection circuitry includes:  
 3        a comparator configured to receive the luminance  
 4 component of the electrical signals and generate a first  
 5 output signal representative of a portion of the total image  
 6 area;  
 7        an integrator, connected to the comparator, for  
 8 receiving the first output signal from the comparator and  
 9 generating a second output signal representative of the  
 10 actual image area; and  
 11        an analog to digital converter which receives the  
 12 second output signal from the integrator and generates a  
 13 digital signal, representative of the actual image area for  
 14 selecting data associated with one of the plurality of  
 15 predefined shutter response areas stored in said memory.

1        6. The apparatus of claim 1 wherein the image  
 2 sensor includes a charge-coupled device having an array of  
 3 photoelectric cells.

1 7. A medical instrumentation system comprising:  
 2 a medical viewing instrument for viewing an object  
 3 under observation;  
 4 an electronic camera optically coupled to the  
 5 medical viewing instrument, for generating electrical  
 6 signals representative of an actual image viewed by the  
 7 electronic camera said electronic camera associated with an  
 8 electronic shutter which controls an image sensor;  
 9 image size detection circuitry, responsive to  
 10 electrical signals received from the electronic camera, for  
 11 determining an actual image area within a total image area  
 12 of the image sensor, and generating a control signal, based  
 13 on the actual image area, for controlling the electronic  
 14 shutter.

1 8. The medical instrumentation system of claim 7  
 2 wherein the electronic camera has a plurality of predefined  
 3 shutter response areas, each shutter response area defining  
 4 different portions of the total image area of the image  
 5 sensor, said control signal selecting one of the shutter  
 6 response area, and said electronic shutter controlling said  
 7 image sensor in response to the selected one of the shutter  
 8 response areas.

1 9. The medical instrumentation system of claim 8  
 2 further comprising a processor and a memory for storing data  
 3 associated with the plurality of predefined shutter response  
 4 areas of the electronic camera.

1        10. The medical instrumentation system of claim 9  
2 wherein the electrical signals includes a luminance  
3 component used by the image size detection circuitry to  
4 determine the portion of the total image area of the image  
5 sensor containing the actual image.

1        11. The medical instrumentation system of claim 10  
2 wherein the image detection circuitry includes:  
3        a comparator configured to receive the luminance  
4 component of the electrical signals and generate a first  
5 output signal representative of a portion of the total image  
6 area;  
7        an integrator, connected to the comparator, for  
8 receiving the first output signal from the comparator and  
9 generating a second output signal representative of the  
10 actual image area; and  
11        an analog to digital converter which receives the  
12 second output signal from the integrator and generates a  
13 digital signal, representative of the actual image area for  
14 selecting data associated with one of the plurality of  
15 predefined shutter response areas stored in said memory.

1        12. The medical instrumentation system of claim 7  
2 wherein the image sensor includes a charge-coupled device  
3 having an array of photoelectric cells.

1           13. A method of controlling an electronic shutter  
 2 used with an image sensor of an electronic camera, the  
 3 method comprising:  
 4           receiving electrical signals from the electronic  
 5 camera,  
 6           determining, in response to the electrical signals,  
 7 an actual image area within a total image area of the image  
 8 sensor; and  
 9           generating, based on the determined actual image  
 10 area, a control signal for controlling the electronic  
 11 shutter.

1           14. The method of claim 13 wherein the electronic  
 2 camera has a plurality of predefined shutter response areas,  
 3 each shutter response area defining different portions of  
 4 the total image area of the image sensor, and controlling  
 5 the electronic shutter further includes selecting one of the  
 6 shutter response areas.

1           15. The method of claim 14 wherein the electrical  
 2 signals includes a luminance component for determining the  
 3 portion of the total image area of the image sensor  
 4 containing the actual image.

09177837 103358

1 16. The method of claim 15 wherein determining an  
2 actual image area occupying a total image area of the image  
3 sensor includes:

4 comparing the luminance component of the electrical  
5 signals with a predetermined threshold value and generating  
6 a first analog output signal representative of a portion of  
7 the actual image area occupying the total image area;

8 integrating the first output signal and generating a  
9 second analog output signal representative of the actual  
10 image area; and

11 converting the second analog signal to a digital  
12 signal representative of the actual image area for selecting  
13 data associated with one of the plurality of predefined  
14 shutter response areas.

1 17. The method of claim 13 wherein the image sensor  
2 includes a charge-coupled device having an array of  
3 photoelectric cells.